

Meet your new dimmer. It is equipped with all of the features found in the original 360 series dimmers plus some added benefits that are sure to help continue this products long run as the industry leader in tree-mount dimmers.

ULD SERIES



Featuring:

Overtemp/Overvoltage Protection

4 & 6 Channel Models

Selectable Curves

25 Amp SSR Power Device

Display Based Menu System

Professional Quality Noise Filtering

Leprecon LLC
P. O. Box 430
10087 Industrial Drive
Hamburg, MI 48139 USA
PH 810-231-9373
FAX 810-231-1631
lepls@leprecon.com



www.leprecon.com

INTRODUCING THE ULD SERIES FROM LEPRECON

Leprecon has expanded their line of industry leading tree-mount dimmers with the addition of the ULD series. Each dimmer is equipped with dual 25 amp SSR's and illuminated magnetic breakers, not to mention over volt/over temp protection. Fully encapsulated chokes come standard with every dimmer to further ensure quiet operation. Through the display based menu system, each channel can be defined as either a non-dim, fluorescent or fixed intensity level. The new ULD-360 has all of the features found in the original 360 series dimmers plus some added benefits that are sure to help continue the products long run as the industry leader in tree-mount dimmers.

ULD 360 TREE-MOUNT DIMMERS

	ULD-360 Stage Pin	ULD-360-HP Stage Pin	ULD-360 Duplex	ULD-360-HP Duplex
Channels	6	6	6	6
Control Protocol	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR
Illuminated Magnetic Breakers**	15 Amp	2/15 Amp	15 Amp	2/15 Amp
Overtemp/Overvolt Pack Protection	Yes	Yes	Yes	Yes
Max Wattage Per Pack @ 120 Volts	1800	3600	1800	3600
Max Wattage Per Channel	1800	1800	1800	1800
Power Input	Single Edison Cord	Two Edison Cords	Single Edison Cord	Two Edison Cords
Programmable Non-Dim Channels	Yes	Yes	Yes	Yes
Selectable Intensity Per Channel	Yes	Yes	Yes	Yes
Power Devices 25 Amp SSR/Channel	Yes	Yes	Yes	Yes
Encapsulated Chokes	Yes	Yes	Yes	Yes
Weight-lbs	8.35	10.35	8.35	10.35
Weight-lbs-Packaged	10	12	10	12
Length, Width, Depth-Inches	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05



ULD 340 TREE-MOUNT DIMMERS

	ULD-340 Stage Pin	ULD-340-HP Stage Pin	ULD-340 Duplex	ULD-340-HP Duplex	ULD-340 Twist-Lok	ULD-340-HP Twist-Lok
Channels	4	4	4	4	4	4
Control Protocol	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR	DMX-512 (M/F) 5 Pin XLR
Illuminated Magnetic Breakers**	15 Amp	2/15 Amp	15 Amp	2/15 Amp	15 Amp	2/15 Amp
Overtemp/Overvolt Pack Protection	Yes	Yes	Yes	Yes	Yes	Yes
Max Wattage Per Pack @ 120 Volts	1800	3600	1800	3600	1800	3600
Max Wattage Per Channel	1800	1800	1800	1800	1800	1800
Power Input	Single Edison Cord	Two Edison Cords	Single Edison Cord	Two Edison Cords	Single Edison Cord	Two Edison Cords
Programmable Non-Dim Channels	Yes	Yes	Yes	Yes	Yes	Yes
Selectable Intensity Per Channel	Yes	Yes	Yes	Yes	Yes	Yes
Power Devices 25 Amp SSR/Channel	Yes	Yes	Yes	Yes	Yes	Yes
Encapsulated Chokes	Yes	Yes	Yes	Yes	Yes	Yes
Weight-lbs	8.35	10.35	8.35	10.35	8.35	10.35
Weight-lbs-Packaged	10	12	10	12	10	12
Length, Width, Depth-Inches	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05	14.15 x 5.82 x 4.05

**20 amp models available. Call factory for pricing and availability.



Leprecon
Lighting for Professionals



FULL TWO YEAR WARRANTY

For a period of two years from the date of sale, Leprecon, LLC, will replace any defective parts and will repair any defective module returned to the factory prepaid, without charge for parts or labor. Please consult your dealer for full warranty details.